



**GIG** VISION **GEN<i>i</i>CAM**



### sensor information

sensor	ams (CMOSIS) CMV4000
resolution	2048 × 2048 px
exposure time	0,02 ... 1000 ms
color filter	RGB Bayer Mosaic
pixel size	5.5 × 5.5 µm
shutter type	Global shutter
sensor type	1" CMOS

### acquisition formats

image formats, interface	Full Frame, 2048 × 2048 px, max. 56 fps
frame rate max.	
image formats, acquisition	Full Frame, 2048 × 2048 px, max. 180 fps
frame rate max. (Burst Mode)	
pixel formats	BayerGB8 BayerGB10 BayerGB12

### image preprocessing

analog controls	Gain (0 ... 12 dB) Offset (0 ... 255 LSB)
color models	Raw Bayer

### interfaces and connectors

data interface	Dual Gigabit Ethernet, Transfer rate 2000 Mbits/sec, Connector: 2 x 8P8C Modular Jack (RJ45), screwable type
process interface	M8 / 8 pins
power supply	M8 / 3 pins

### mechanical data

lens mount	C-mount (F-mount on request)
width	52 mm
height	52 mm
depth	55 mm

### mechanical data

weight	≤ 232 g
material	housing: aluminum

### electrical data

voltage supply	20 ... 30 V DC (external power supply)
range +Vs	38 ... 57 V DC (Power over Ethernet)
power consumption	approx. 8,4 W @ 24 VDC and 56,0 fps approx. 9,5 W @ 48 VDC (PoE) and 56,0 fps

### environmental conditions

operating temperature	+5 ... +50 °C
humidity	10 ... 90 % (non-condensing)
protection class	IP 40

### conformity

conformity	CE RoHS FCC EAC
------------	--------------------------

### dimension drawing

