

ITEM 092657 35POL/15M/METALLAUSFUEHRUNG

Description	Technical data	Accessories	Downloads



Features

- Extension cable
- > Flange plug connector with socket contacts, 35-pin
- Plug connector with male contacts, 35-pin
- Bayonet plug lock
- PUR cable
- Cable length 15 m, straight

Mechanical values and environment

Sheath material	PUR
Drag chain suitability	No
Ambient temperature	
Dynamic	-10 +70 °C
static	-40 +80 °C
Number of conductors	35
Type of cable	straight
Cable length	15 m


Cable diameter	10,4 mm			
Conductor cross-section	4 x 0.34 mm ² + 4 x 0.34 mm ² + 27 x 0.14 mm ²			
Bending radius				
Dynamic	≥ 15 x cable diameter			
Interlocking				
Flange plug connector/plug connector	Bayonet			
	Connection 1			
Degree of protection	IP 67 [1]			
Designation of plug connector	UT00			
Connection	Flange plug connector			
Connection type	Socket contacts			
Cable outlet	straight			
Number of pins	35			
Plug lock	Bayonet			
	Connection 2			
Degree of protection	IP 67 [2]			
Designation of plug connector	UT06			
Connection	Plug connector			
Connection type	Male contact			
Cable outlet	straight			
Number of pins	35			
Plug lock	Bayonet			

Electrical connection ratings

Cable shielding	Yes
-----------------	-----

[1, 2] In the inserted state

Dimension drawing



Steckerbelegung: 6		Steckerbelegung:			Steckerbelegung:			
Kontakt	Querschnitt	Adernfarbe	Kontakt	Querschnitt	Adernfarbe	Kontakt	Querschnitt	Ademfarbe
Pin	mm²		Pin	mm²		Pin	mm²	
7	8	9	7	8	9	7	8	9
Α	0,14	BNBU	N	0,14	BNGN	b	0,14	BKWH
В	0,14	BUWH	Р	0,34	GN	С	0,14	BKBN
C	0,14	GNWH	R	0,34	YEWH	d	0,14	GNGY
D	0,14	YEWH	S	0,14	BNYE	е	0,14	YEGY
E	0,14	GYWH	Т	0,14	BNGY	f	0,14	GNPK
F	0,14	WKPK	U	0,14	BNPK	g	0,14	YEPK
G	0,14	BK	V	0,34	WH	h	0,14	GNBU
Н	0,14	VT	W	0,34	BN	i	0,14	YEBU
J	0,14	GYPK	х	0,34	RD	j	0,14	RDGN
K	0,34	GY	Y	0,34	BU	k	0,14	RDYE
L	0,34	PK	Z	0,14	RDWH	m	0,14	BKGN
M	0,14	RDBU	a	0,14	BNRD			

Legende

- 1 Flange plug connector with socket contacts
- 2 Plug connector with male contacts
- 3 Pin assignment 1:1, inner screens not connected, outer screen connected to plug housing
- 4 Cable length: 15m
- Wires: 4×0.34 mm², 4×0.34 mm², 27×0.14 mm², plug connector: Number of pins 35,
- version: Metal
- 6 Connector assignment:
- 7 Contact pin
- 8 Cross-section mm²
- 9 Conductor coloring