

AV98A672

CONNECTION TECHNOLOGY • CONNECTORS / PLUGS

ipf cable sockets are used primarily for establishing the electrical connection of sensors. Their features are characterized by rugged design, the highest protection classes (IP67 | IP68 | IP69K) and, if desired, with 360° shielding. With the features: bus-ready, suitable for use with drag chains and robots, resistance to oil and chemicals, resistance to welding sparks, their resistance to cleaning agents or high-pressure and steam-jet cleaning, the expanded temperature range of up to +230°C, the rapid interconnection technology and special data transmission properties, the cable sockets meet all requirements in automation technology.



MECHANICAL DATA

	1.5 mm
	M16
Ambient temperature	-25 °C ... 80 °C
Contact body material	Brass
Contact coating material	Gold
Degree of protection (IP)	IP67
Insulating body material	PA
Number of wires	4
Type of mechanical connection	Screw fitting M16
Wire cross section	0.34 mm ²
With thread	Yes

ELECTRICAL DATA

	0.5 m
Ampacity	4 A
Number of pins	4
Rated voltage	250 V
Suitable for self-assembly	Yes
Type of electrical connection, inner side	Wire
Type of electrical connection, outer side	M12
Type of plug-in contact, outer side	Male (plug)

OTHER DATA

Version	IV000362
---------	----------

DIMENSIONAL DRAWING

INSTALLATION

DISPOSAL



Mounting / Installation may only be carried out by a qualified electrician!



SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!