

## VK00382D

### CONNECTION TECHNOLOGY • CABLE SOCKETS FIELD-ATTACHABLE

ipf cable sockets are used primarily for establishing the electrical connection of sensors. Their features are characterized by rugged design, the highest protection classes (IP67 | IP68 | IP69K) and, if desired, with 360° shielding. With the features: bus-ready, suitable for use with drag chains and robots, resistance to oil and chemicals, resistance to welding sparks, their resistance to cleaning agents or high-pressure and steam-jet cleaning, the expanded temperature range of up to +230°C, the rapid interconnection technology and special data transmission properties, the cable sockets meet all requirements in automation technology.



#### MECHANICAL DATA

Contact body material	CuZn
Degree of protection (IP)	IP67
Housing material	PBT
Number of wires	8
Perm. ambient temperature of cable, fixed cable	-25 °C ... 85 °C
Positioning of cable feed, field side	Straight
Suitable for trailing chain	Yes
Wire cross section	0.5 mm <sup>2</sup>


#### ELECTRICAL DATA

Number of pins	8
Rated current I <sub>n</sub>	2 A
Rated voltage	30 V
Shielded	No
Suitable for self-assembly	Yes
Type of electrical connection, field side	M12
Type of plug-in contact, field side	Female (socket)
With LED display	No


#### OTHER DATA

Flame resistant	No
Halogen-free	No
IR-networked	No
Oil and cooling lubricants	Yes
Welding area	Yes

## CONNECTION



## DIMENSIONAL DRAWING



## INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!

## DISPOSAL



## SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!