IPF ELECTRONIC

VK003S75

CONNECTION TECHNOLOGY • CABLE SOCKETS FIELD-ATTACHABLE

ipf cable sockets are used primarily for establishing the electrical connection of sensors. Their features are characterized by rugged design, the highest protection classes (IP67 | IP68 | IP69K) and, if desired, with 360° shielding. With the features: bus-ready, suitable for use with drag chains and robots, resistance to oil and chemicals, resistance to welding sparks, their resistance to cleaning agents or high-pressure and steam-jet cleaning, the expanded temperature range of up to +230°C, the rapid interconnection technology and special data transmission properties, the cable sockets meet all requirements in automation technology.



MECHANICAL DATA

Welding area

Degree of protection (IP)	IP67
Number of wires	4
Perm. ambient temperature of cable, fixed cable	-25 °C 85 °C
Positioning of cable feed, field side	Straight
Suitable for trailing chain	Yes
ELECTRICAL DATA	
Line diameter	5.1 mm
Number of pins	4
Rated current In	4 A
Rated voltage	32 V
Shielded	No
Suitable for self-assembly	Yes
Type of electrical connection, field side	M8
Type of plug-in contact, field side	Female (socket)
With LED display	No
OTHER DATA	
Flame resistant	No
Halogen-free	No
IR-networked	No
Oil and cooling lubricants	Yes

Yes



CONNECTION



Colors: 1 = BN (brown), 2 = WH (white), 3 = BU (blue), 4 = BK (black) **Functions:**

DIMENSIONAL DRAWING

INSTALLATION

DISPOSAL



Mounting / Installation may only be carried out by a qualified electrician!



SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!