

VK15HF21

CONNECTION TECHNOLOGY • CABLE SOCKETS /CONNECTORS TWO-SIDED PRE-ASSEMBLED

ipf cable sockets are used primarily for establishing the electrical connection of sensors. Their features are characterized by rugged design, the highest protection classes (IP67 | IP68 | IP69K) and, if desired, with 360° shielding. With the features: bus-ready, suitable for use with drag chains and robots, resistance to oil and chemicals, resistance to welding sparks, their resistance to cleaning agents or high-pressure and steam-jet cleaning, the expanded temperature range of up to +230°C, the rapid interconnection technology and special data transmission properties, the cable sockets meet all requirements in automation technology.

MECHANICAL DATA

Ambient temperature	-20 °C ... 150 °C
Cable length	1.5 m
Contact body material	CuZn
Contact coating material	Gold
Degree of protection (IP)	IP65
Housing material	PBT
Increased ambient temperature > 90°C	Yes
Material of cable sheath	PTFE
Max. tightening torque	1 Nm
Number of wires	4
Perm. ambient temperature of cable, fixed cable	-190 °C ... 260 °C
Positioning of cable feed, field side	Angled
Positioning of cable feed, housing side	Straight
Seawater-resistant	Yes
Wire assembly	7 x 0.254mm
Wire cross section	0.34 mm ²

ELECTRICAL DATA

Flow resistance	5 mOhm
Line diameter	3.8 mm
Number of pins	4
Number of pins, housing side	4
Rated current I _n	4 A
Rated voltage	250 V
Shielded	No
Type of electrical connection, field side	M12
Type of electrical connection, housing side	M12
Type of plug-in contact, field side	Female (socket)
Type of plug-in contact, housing side	Male (plug)
With LED display	No


OPTICAL DATA

Degree of soiling	3
-------------------	---

OTHER DATA

Flame resistant	No
Free of LABS	Yes
Halogen-free	No
Hydrolysis-proof	Yes
IR-networked	No
Ozone and UV-resistant	Yes
RoHs-compliant	Yes
Silicone-free	Yes
Welding area	Yes

CONNECTION



Colors: A: 1 = BN (brown), 2 = WH (white), 3 = BU (blue), 4 = BK (black)

B: 1 = BN (brown), 2 = WH (white), 3 = BU (blue), 4 = BK (black) **Functions:**

DIMENSIONAL DRAWING

INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL



SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!