

VK200625

CONNECTION TECHNOLOGY • CABLE SOCKETS / CONNECTORS ONE-SIDED PRE-ASSEMBLED

ipf cable sockets are used primarily for establishing the electrical connection of sensors. Their features are characterized by rugged design, the highest protection classes (IP67 | IP68 | IP69K) and, if desired, with 360° shielding. With the features: bus-ready, suitable for use with drag chains and robots, resistance to oil and chemicals, resistance to welding sparks, their resistance to cleaning agents or high-pressure and steam-jet cleaning, the expanded temperature range of up to +230°C, the rapid interconnection technology and special data transmission properties, the cable sockets meet all requirements in automation technology.



MECHANICAL DATA

| Cable length | 2 m |
|-------------------------------------------------|--------------------|
| Degree of protection (IP) | IP67 |
| Material of cable sheath | PUR (Polyurethane) |
| Number of wires | 5 |
| Perm. ambient temperature of cable, fixed cable | -25 °C 90 °C |
| Positioning of cable feed, field side | Straight |
| Positioning of cable feed, housing side | Straight |
| Suitable for trailing chain | Yes |
| Wire assembly | 16 x 0.2mm |
| Wire cross section | 0.34 mm² |

ELECTRICAL DATA

| Line diameter | 5.4 mm |
|---------------------------------------------|--------------------|
| Number of pins | 5 |
| Rated current In | 4 A |
| Rated voltage | 60 V |
| Type of electrical connection, field side | M12 |
| Type of electrical connection, housing side | Free conductor end |
| Type of plug-in contact, field side | Female (socket) |
| With LED display | No |

OTHER DATA

| - · · · · · · · · · · · · · · · · · · · | |
|-----------------------------------------|---------------------------------|
| Flame resistant | In accordance with EN 60332-2-2 |
| Free of LABS | Yes |
| Halogen-free | Yes |
| Hydrolysis-proof | Yes |
| IR-networked | No |
| Oil and cooling lubricants | Yes |
| Ozone and UV-resistant | Yes |
| RoHs-compliant | Yes |
| Silicone-free | Yes |
| | |



OTHER DATA

Suitable for trailing chain and torsion resistant

Yes

| Welding area | Yes |
|--------------|-----|
|--------------|-----|


CONNECTION



Colors: 1 = BN (brown), 2 = WH (white), 3 = BU (blue), 4 = BK (black), 5 = GY (gray)

Functions:

DIMENSIONAL DRAWING



INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL



SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!