

Datasheet - NBG 664/NM

Command and signalling devices / Assembly housing NBG / NBG



(Minor differences between the printed image and the original product may exist!)

- for application in food producing machinery
- Enclosure seal for food machinery

Ordering details

Product type description	NBG 664/NM
Article number	101182351
EAN Code	
eCl@ss	27-37-12-05

Approval

Approval



BG

Global Properties

Permanent light	NBG - Aufbaugehäuse
Number of command positions	4
Materials	
- Material of the housings	Stainless steel (V4A)
- Housing color of upper part	■ Silver
- color of base part	■ Silver
Color	
- Colour of the bellows	Grey
Weight	1800
Number of through-holes for the cable gland	2
Protective collar in housing cover (Y/N)	No

Mechanical data

Knockout holes for cable gland (Y/N)	No
Position of the cable gland	mounting holes

Ambient conditions

Ambient temperature	
- Min. environmental temperature	-25
- Max. environmental temperature	+80
Protection class	IP67. IP69K

Dimensions

Dimensions

- Width	110 mm
- Height	86.5 mm
- Depth	324 mm
Diameter of the through-holes for cable glands	20.3
Center-to-center distance of the drilled holes for the command posts	71

notice

notice

Hygiene-compliant IP69 cable gland in 1.4305 upon request

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The data and values have been checked thoroughly. Technical modifications and errors excepted.

Generiert am 13.02.2019 - 12:52:31h Kasbase 3.3.0.F.64I