


**IMPACT67 COMPACT MODULE, PLASTIC**


Ethernet/IP, 16 dig Out

Digital outputs  
DO16 - 0.5 A

Connection cables are in the online shop under "Connection Technology". Housing fully potted.

[Link to Product](#)**Illustration**

Product may differ from Image

**Approvals****More Info**



### Connections

Fieldbus	Ethernet 10/100 Mbit/s; M12, D-coded
Sensor-system/actuator supply	7/8", 5-pole, 2 × max. 9 A
I/O ports	M12, 5-pole, A-coded

### General data

Protection	IP67
Mounting method	2 hole screw mounting, compatible with I/O modules of MVK model range
Temperature range	0...+55 °C (storage temperature -25...+70 °C)
Dimensions H × W × D	39×63×225 mm

### EtherNet/IP

Addressing	DHCP, BOOTP or IP address by rotary switch
------------	--

### Output

Switching current per output	max. 0.5 A (short-circuit and overload protected)
------------------------------	---

### Diagnostic

Communication status	via LED
Diagnostic via LED	per module and channel
Diagnostic via BUS	per module and channel
Monitoring - under voltage	yes
Monitoring - no voltage	yes
Short-circuit and overload	yes

### Commercial data

country of origin	DE
customs tariff number	85389099
EAN	4048879051927
eClass	27242604
Packaging unit	1