


**MVK+ MPNIO DI8 DI8 IRT PUSH PULL**


MVK ProfiNet, metal, galvanic separation

Digital inputs/outputs  
DI8 DI8 (IRT)  
Push Pull

Connection cables are in the online shop under "Connection Technology". Housing fully potted.

[Link to Product](#)**Illustration**

Product may differ from Image

**Approvals****More Info**



### Input

Sensor supply US	24 V DC (EN 61131-2), max. 200 mA (M12 female), short-circuit and overload protected
Type	for 3-wire sensors or mechanical switches, PNP

### Connections

Fieldbus	Ethernet 10/100 Mbit/s; Push Pull RJ45 Data connector
Sensor-system/actuator supply	Push Pull Power connector, max. 12 A
I/O ports	M12, 5-pole, A-coded

### General data

Protection	IP67
Mounting method	2-hole screw mounting
Temperature range	0...+55 °C (storage temperature -20...+70 °C)
Dimensions H × W × D	42.7×63×225 mm

### PROFINET

FSU (Fast-Start-Up)	max. 500 ms
Shared Device/Input	yes, for 2 controls
PROFINET Netload Class	III
Specification	V2.2, Conformance Class C (IRT)
MRP	yes
Addressing	DCP

### Parameterization

PIN 4	Input
PIN 2	Input

### Diagnostic

Communication status	via LED
Diagnostic via LED	per module and channel
Diagnostic via BUS	per module and channel
Monitoring - under voltage	yes
Monitoring - no voltage	yes
Short-circuit and overload	yes
Actuator warning	per channel via LED and BUS
Cable break	per port

### Commercial data

country of origin	DE
customs tariff number	85389099
EAN	4048879563369

---

eClass	27242604
Packaging unit	1

---