

## EVOLUTION+ POWER SUPPLY 3-PHASE,

Alarm Contact and varnished PCB


INPUT : 3×360...520 V AC/480...745 V DC

OUTPUT : 48...56 V DC

Current : 20 A


### [Link to Product](#)

#### Illustration



Product may differ from Image

#### Approvals



### Input

Input voltage	3 × 324...572 V AC/480...745 V DC
Input current	3 × 1.9 A
Frequency	50...60 Hz
Primary fusing external	max. 3 × 20 A

### General data

Standards	EN 60950-1, EN 61204-3, EN 55022 B, EN 61000-3-2
Relative humidity	5...95%, no condensation
Protection	Varnished board
Protection	IP20
Efficiency	92.5% (3 × 360 V AC); 90.5% (3 × 520 V AC)
Connection	Screw terminals
Mounting method	DIN-rail mountable TH35 (EN 60715)
Dimensions H × W × D	132×164×142 mm
Temperature range	-25...+70 °C (storage temperature -40...+85 °C)

### Output

Output voltage	48 V DC (SELV), ±1%; 48...56 V adjustable
Output current	20 A (+55 °C); 15 A (+70 °C)
Power Boost	I <sub>out</sub> N × 150% (min. 4 s)
Mains failure bridging time	min. 17 ms (400 V AC)
Ripple	max. 50 mVrms
Unit protection	Short-circuit and overload protected
Spikes	max. 100 mV p-p
LED display	LED (green): OK; LED (red): overload
Parallel usage/serial usage	max. 5 units/no
Alarm output	electronic relay max. 30 V DC/0.1 A, group alarm

### Commercial data

country of origin	CZ
customs tariff number	85044090
EAN	4048879384803
eClass	27049002
Packaging unit	1