


MTL 1-PHASE CONTROL AND ISOLATION TRANSFORMER

P: 63VA IN: 230/400VAC +/- 15VAC OUT: 2x115VAC

Single-phase - Control and Isolation Transformers
63 VA
Isolation class T 60/B

[Link to Product](#)

Illustration



Product may differ from Image

Approvals



Input

Input voltage	230/400 ±15 V AC
Frequency	50...60 Hz
Input current	0.4 A (230 V AC); 0.23 A (400 V AC)
Inrush current	5.35 A (230 V AC); 3.09 A (400 V AC)
Short-circuit current	7.2 A (230 V AC); 4.16 A (400 V AC)

Technical Data

LED display	LED (green) for input voltage
-------------	-------------------------------

General data

Test isolation voltage	4 kV (prim./sec.)
Standards	EN 61558-1, EN 61558-2-4, EN 62041 category 0
Drill hole Ø	5.5×9 mm
Mounting method	DIN-rail mountable TH35-15 (EN 60715) or for key-hole mounting
Fixing centers a × b × c	96×60×5.5 mm
Dimensions H × W × D	108×87×116 mm
Temperature range	-20...+60 °C, no condensation

Output

Output voltage	1 × 230, 1 × 115, 2 × 115 V AC
Output rating	63 VA

Commercial data

country of origin	CZ
customs tariff number	85043180
EAN	4048879078214
eClass	27031302
Packaging unit	1