



Product may differ from Image

Approvals



Input

| | |
|-----------------------|------------------------------------|
| Input voltage | 230/400 ±15 V AC |
| Frequency | 50...60 Hz |
| Inrush current | 83 A (230 V AC); 42 A (400 V AC) |
| Short-circuit current | 165 A (230 V AC); 94 A (400 V AC) |
| Input current | 4.6 A (230 V AC); 2.7 A (400 V AC) |

General data

| | |
|--------------------------|---|
| Standards | EN 61558-1, EN 61558-2-4, EN 62041 category 0 |
| Test isolation voltage | 5.8 kV (prim./sec.) |
| Temperature range | -20...+40 °C, no condensation |
| Dimensions H × W × D | 156×150×146 mm |
| Fixing centers a × b × c | 134×122×7 mm |
| Drill hole Ø | 7×11 mm |
| Mounting method | Key-hole mounting |

Output

| | |
|----------------|--------------------------------|
| Output voltage | 1 × 230, 1 × 115, 2 × 115 V AC |
| Output rating | 1 000 VA |

Commercial data

| | |
|-----------------------|---------------|
| country of origin | CZ |
| customs tariff number | 85043180 |
| EAN | 4048879366847 |
| eClass | 27031302 |
| Packaging unit | 1 |