

PMI 638 Control

264638



Operator & control touch panel with 15" (38cm) screen diagonal, CODESYS Runtime & TargetVisu pre-installed and licensed, Mastersystems: CANopen, ModbusTCP, Screen: TFT display (65k colors), LED backlight, Resolution: 1024x768 pixels (16:9 widescreen), Input: Resistive Foiltouchscreen, Frontdesign: Standard grey, Processor: Pilz CPU Board 1.3GHz (x86), Memory: RAM: 512MB; Flash: 512MB, Power supply: 24V DC, Power consumption: 12.7W (24VDC), Interfaces: 1x RS232; 2x RJ45 ETH; 1x SD Card; 3x USB 2.0, Fielbus interface: CAN, Operating system: Windows Embedded Compact 7 (Professional)

Технические характеристики

Версия товара:	1.0
Согласования:	CE;cULus Listed
Размер по ширине:	412.0 mm
Размер по высоте:	332.0 mm
Размер по глубине:	81.9 mm
Вес брутто:	6860 g
Вес нетто:	4510 g
Окружающая температура:	0 - 50 °C

Дополнительные принадлежности




261905

RT-Licence PVIS OPC-Srv f.PMI, PtoP



261906

RT-Licence PVIS OPC-Srv f.PMI, 8 devices



269700

power connector PMI (3 pcs)



310300

Serial programming cable

265010

Zenon Operator Dev 1024

265210

Zenon Operator RT PMI
