

PMI v507

265507



Operator touch panel with 7"(18cm) screen diagonal, Pre-installed PASvisu runtime environment, Runtime licence PMI for 500 external variables included, Screen: TFT display (m16.2 colors), LED backlight, Resolution: 800x480 pixels (16:9 widescreen), Input: Capacitive glass touchscreen, Frontdesign: Standard black, Processor: Pilz TI OMAP CPU Board 1GHz, Memory: RAM: 256MB; Flash: 512MB, Power supply: 24V DC, Power consumption: 6.5W (24VDC), Interfaces: 1x RS232; 1x RJ45 ETH; 1x SD Card; 2x USB 2.0, Operating system: Windows Embedded Compact 7 (Professional)

Технические характеристики

Согласования:	CE;cULus Listed
Размер по ширине:	216.0 mm
Размер по высоте:	153.0 mm
Размер по глубине:	65.4 mm
Вес брутто:	2400 g
Вес нетто:	1390 g
Окружающая температура:	0 - 50 °C

Дополнительные принадлежности




261905

RT-Licence PVIS OPC-Srv f.PMI, PtoP



261906

RT-Licence PVIS OPC-Srv f.PMI, 8 devices



269700

power connector PMI (3 pcs)



269701

seal for PMlvisu, PMlopen, PMlmicro



310300

Serial programming cable



313100

SD Memory Card 512MB

265010

Zenon Operator Dev 1024

265210

Zenon Operator RT PMI
