

## PMI v512

265512



Operator touch panel with 12" (31cm) screen diagonal, Pre-installed PASvisu runtime environment, Runtime licence PMI for 500 external variables included, Screen: TFT display (m16.2 colors), LED backlight, Resolution: 1280x800 pixels (16:9 widescreen), Input: Capacitive glass touchscreen, Frontdesign: Standard black, Processor: Pilz TI OMAP CPU Board 1GHz, Memory: RAM: 256MB; Flash: 512MB, Power supply: 24V DC, Power consumption: 8.9W (24VDC), Interfaces: 1x RS232; 1x RJ45 ETH; 1x SD Card; 2x USB 2.0, Operatingsystem: Windows Embedded Compact 7 (Professional)

## Технические характеристики

Согласования:	CE;cULus Listed
Размер по ширине:	332.0 mm
Размер по высоте:	222.0 mm
Размер по глубине:	63.4 mm
Вес брутто:	5300 g
Вес нетто:	2450 g
Окружающая температура:	0 - 50 °C

## Дополнительные принадлежности




261905

RT-Licence PVIS OPC-Srv f.PMI, PtoP



261906

RT-Licence PVIS OPC-Srv f.PMI, 8 devices



269700

power connector PMI (3 pcs)



269701

seal for PMlvisu, PMlopen, PMlmicro

---



310300

Serial programming cable

---



313100

SD Memory Card 512MB

---

265010

Zenon Operator Dev 1024

---

265210

Zenon Operator RT PMI

---