PILZ
THE SPIRIT OF SAFETY

PSEN cs4.1 M12/8-1.5m/PSEN cs4.1 1unit 541114

Non-contact coded safety switch for position monitoring of movable guards according to EN 60947-5-3; two safe outputs; connector M12/8pin with 1.5m cable. For applications up to SILCL 3 resp PLe bzw. Cat4 ;IP 67, typical switching distance 11mm, Sao=8mm, Sar=20mm packaging unit = 1piece fully coded switch and 1 piece actuator. Teach- in of 8 other actuators possible.

Технические характеристики

Согласования:	CE;cULus Listed;TÜV;FCC;IC
Принцип датчика:	Транспондер
Тип программирования:	Полное программирование
Число выходов OSSD:	2
Число входов:	2
Тип соединения:	M12, 8pol. male
Напряжение питания (V):	24,0
Тип питающего напряжения:	DC
потребляемая мощность DC:	1.0 W
Гарантированная дальность переключения:	8.0 mm
Гарантированное расстояние выброса:	20.0 mm
Тип защиты, корпус:	IP6K9K
Размер по ширине:	26.0 mm
Размер по высоте:	37.0 mm
Размер по глубине:	18.0 mm
Вес брутто:	140 g
Вес нетто:	110 g
Окружающая температура:	-25 - 70 °C

Дополнительные компоненты

	533150	PSEN cable M8-8sf, 2m
	533151	PSEN cable M8-8sf, 5m
	533152	PSEN cable M8-8sf, 10m
	533153	PSEN cable M8-8sf, 20m
	533154	PSEN cable M8-8sf, 30m

Дополнительные принадлежности

	533150	PSEN cable M8-8sf, 2m
	533151	PSEN cable M8-8sf, 5m
	533152	PSEN cable M8-8sf, 10m

	533153	PSEN cable M8-8sf, 20m
	533154	PSEN cable M8-8sf, 30m
	533155	PSEN cable M8-8sf M8-sm, 0.5m
	533156	PSEN cable M8-8sf M8-8sm, 1m
	533157	PSEN cable M8-8sf M8-8sm, 2m
	540329	PSEN converter M8-8sf -- M12-8sm
	773603	PDP67 F 4 code
	540340	PSEN cable M12-8sf M12-8sm, 2m
	540341	PSEN cable M12-8sf M12-8sm, 5m

	540343	PSEN cable M12-8sf M12-8sm, 20m
	540344	PSEN cable M12-8sf M12-8sm, 30m
	540342	PSEN cable M12-8sf M12-8sm, 10m
	540130	SDD ES ETH
	540132	SDD ES PROFIBUS
	540337	PSEN Y junction M8-M12/M12 PIGTAIL