

PSEN sl-0.5p 4.1

570578



Safety gate system with magnetic interlock, IP67, 8pin M12 connector (male). 2 safe semiconductor outputs (OSSD); Solenoid power 500N (process guarding); 4 LEDs; Applications up to SIL3/PL e/Cat4; additional function: safe semiconductor outputs are high if door is closed (independent from guardlocking function); Content = 1 fully coded Sensor without actuator. Teach-in of new actuators up to 8 times.

## Технические характеристики

|                                     |                            |
|-------------------------------------|----------------------------|
| Гарантированное расстояние выброса: | 15.0 mm                    |
| Согласования:                       | CE;cULus Listed;TÜV;FCC;IC |
| Принцип датчика:                    | Транспондер                |
| Тип программирования:               | Полное программирование    |
| Сила удержания:                     | 500 N                      |
| Число выходов OSSD:                 | 2                          |
| Число входов:                       | 3                          |
| Тип соединения:                     | M12, 8pol. male            |
| Напряжение питания (V):             | 24,0                       |
| Тип питающего напряжения:           | DC                         |
| потребляемая мощность DC:           | 4.8 W                      |
| Тип защиты, корпус:                 | IP67                       |
| Размер по ширине:                   | 45.0 mm                    |
| Размер по высоте:                   | 122.0 mm                   |
| Размер по глубине:                  | 44.0 mm                    |
| Вес брутто:                         | 630 g                      |
| Вес нетто:                          | 570 g                      |
| Окружающая температура:             | -25 - 55 °C                |

## Дополнительные компоненты



570521

PSEN sl-0.5 2.1 1 actuator

## Дополнительные принадлежности



540319

PSEN cable axial M12 8-pole 3m



540320

PSEN cable axial M12 8-pole 5m



540321

PSEN cable axial M12 8-pole 10m



540322

PSEN cable angle M12 8-pole 3m



540323

PSEN cable angle M12 8-pole 5m



540324

PSEN cable angle M12 8-pole 10m



540325

PSEN cable angle M12 8-pole 30m



540326

PSEN cable axial M12 8-pole 30m



540328

PSEN Y junction M12-M12/M12



570550

PSEN sl bracket swing door



570551

PSEN sl bracket sliding door



540331

PSEN T junction (auxiliary contact) M12



773603

PDP67 F 4 code



540312

PSEN screw M5x20 10pcs



540340

PSEN cable M12-8sf M12-8sm, 2m



540341

PSEN cable M12-8sf M12-8sm, 5m



540343

PSEN cable M12-8sf M12-8sm, 20m

---



540344

PSEN cable M12-8sf M12-8sm, 30m

---



540342

PSEN cable M12-8sf M12-8sm, 10m

---



540333

PSEN cable M12-8sf, 20m

---