

PSEN sl-1.0p 4.1

570678



Safety gate system with magnetic interlock, IP67, 8pin M12 connector (male). 2 safe semiconductor outputs (OSSD); Solenoid power 1000N (process guarding); 4 LEDs; Applications up to SIL3/PL e/Cat4; additional function: safe semiconductor outputs are high if door is closed (independent from guardlocking function); Content = 1 fully coded Sensor without actuator. Teach-in of new actuators up to 8 times.

## Технические характеристики

Гарантированное расстояние выброса:	15.0 mm
Согласования:	CE;cULus Listed;TÜV;FCC;IC
Принцип датчика:	Транспондер
Тип программирования:	Полное программирование
Сила удержания:	1000 N
Число выходов OSSD:	2
Число входов:	3
Тип соединения:	M12, 8pol. male
Напряжение питания (V):	24,0
Тип питающего напряжения:	DC
потребляемая мощность DC:	7.2 W
Тип защиты, корпус:	IP67
Размер по ширине:	45.0 mm
Размер по высоте:	172.0 mm
Размер по глубине:	44.0 mm
Вес брутто:	1190 g
Вес нетто:	1120 g
Окружающая температура:	-25 - 55 °C

## Дополнительные компоненты



570621

PSEN sl-1.0 2.1 1 actuator

## Дополнительные принадлежности



540319

PSEN cable axial M12 8-pole 3m



540320

PSEN cable axial M12 8-pole 5m



540321

PSEN cable axial M12 8-pole 10m



540322

PSEN cable angle M12 8-pole 3m



540323

PSEN cable angle M12 8-pole 5m



540324

PSEN cable angle M12 8-pole 10m



540325

PSEN cable angle M12 8-pole 30m



540326

PSEN cable axial M12 8-pole 30m



540328

PSEN Y junction M12-M12/M12



570550

PSEN sl bracket swing door



570551

PSEN sl bracket sliding door



540331

PSEN T junction (auxiliary contact) M12



773603

PDP67 F 4 code



540312

PSEN screw M5x20 10pcs



540340

PSEN cable M12-8sf M12-8sm, 2m



540341

PSEN cable M12-8sf M12-8sm, 5m



540343

PSEN cable M12-8sf M12-8sm, 20m

---



540344

PSEN cable M12-8sf M12-8sm, 30m

---



540342

PSEN cable M12-8sf M12-8sm, 10m

---



540333

PSEN cable M12-8sf, 20m

---