

Accessories

Motor earthing unit

Motor earthing unit ATEX/IECEX - EExME 12 C



Features

- Ex-approved by ATEX II 2 G Ex db IIC T4 Gb (gas)
- IEC Ex db IIC T4 Gb (gas)
- EG design test certificate
TÜV NORD CERT No. TÜV 02 ATEX 1920 X
IECEX TUN 11.0036X
- Leakage of parasitical shaft currents
- Hollow shaft $\varnothing 20...42$ mm
- Ceramic bearings for higher speeds

Part number

EExME 12 C Motor earthing unit

Description

The motor earthing unit is discharging parasitical shaft currents to avoid damage of the ball bearings.

Technical data

Current load	≤ 1 A ≤ 12 A (short-term)
Operating speed	≤ 9500 rpm
Ambient temperature	$-55...+60$ °C
Admitted shaft load	≤ 150 N axial ≤ 200 N radial
Rotor moment of inertia	3.7 kgcm ²
Operating torque	≤ 15 Ncm
Explosion protection	II 2 G Ex db IIC T4 Gb Ex db IIC T4 Gb
Weight approx.	3.5 kg
Protection DIN EN 60529	IP 56
Shaft type	$\varnothing 20...42$ mm (through hollow shaft)
Material	Housing: aluminium
Resistance	IEC 60068-2-6 Vibration 10 g, 50-2000 Hz IEC 60068-2-27 Shock 100 g, 6 ms
Approvals	CE, ATEX, IECEX

Accessories

Motor earthing unit

Motor earthing unit ATEX/IECEX - EExME 12 C

Dimensions

