



sensor information

sensor	ams (CMOSIS) CMV300
resolution	640 × 480 px
exposure time	0,015 ... 1000 ms
pixel size	7.4 × 7.4 μm
shutter type	Global shutter
sensor type	1/3" CMOS

acquisition formats

image formats, interface frame rate max.	Full Frame, 640 × 480 px, max. 376 fps
pixel formats	Mono8 Mono12 Mono12 Packed

image preprocessing

analog controls	Gain (0 ... 18 dB) Offset (0 ... 255 LSB 12 Bit)
color models	Mono

interfaces and connectors

data interface	Gigabit Ethernet, Transfer rate 1000 Mb/s/sec, Fast Ethernet, Transfer Rate 100 Mb/s/sec, Connector: 8P8C Modular Jack (RJ45), screwable type
process interface	SACC-DSI-M8FS-3CON-M10-L180 SH
power supply	SACC-DSI-M 8MS-6CON-L180 SH

mechanical data

lens mount	C-mount
width	33 mm
height	33 mm
depth	48 mm
weight	≤ 150 g
material	zinc die casting, nickel-plated, IP 40

electrical data

voltage supply	12 ... 24 V DC (external power supply)
range +Vs	36 ... 57 V DC (Power over Ethernet)
power consumption	approx. 3,0 W @ 12 VDC and 376,0 fps approx. 3,6 W @ 48 VDC (PoE) and 376,0 fps

non-volatile memory

flash memory size	128 kB
-------------------	--------

environmental conditions

operating temperature	+5 ... +50 °C
humidity	10 ... 90 % (non-condensing)
protection class	IP 40

digital I/Os

lines	1 input line 3 output lines
-------	--------------------------------

conformity

conformity	CE RoHS KC (MSIP-REI-BkR-VLG-03MCS) EAC
------------	--

dimension drawing

