



C9900-E21x | RFID reader in the CP7xxx Control Panel front

The CP720x and CP770x Panel PCs and the CP790x Control Panels with 15- or 19-inch display without membrane keyboard are available with RFID reader in the front panel. The card reader enables user identification at the device. The RFID module reads Legic transponders at a distance of up to 30 mm. The data are transferred to the PC via USB. The RFID reader is integrated in the Control Panel or the Panel PC behind the front laminate. The print on the front laminate indicates the position of the RFID reader below the display on the right-hand side. IP 65 protection class is maintained and enables operation in harsh industrial environments. The RFID option has no influence on the dimensions of the Control Panel.

C9900-E21x	RFID reader in the CP7xxx Control Panel front
	Legic transponder type
	transponder frequency 13.56 MHz
	integrated in the Control Panel behind the front laminate
	up to 30 mm reading distance
	internally connected via USB interface
	protection class IP 65

Ordering information	RFID reader
C9900-E213	RFID reader for Legic transponder inside the front of a Panel PC CP7202 or CP7702 or of a Control Panel CP7902, integrated behind the front laminate, protection class IP 65, connected internally by USB
C9900-E214	RFID reader for Legic transponder inside the front of a Panel PC CP7203 or CP7703 or of a Control Panel CP7903, integrated behind the front laminate, protection class IP 65, connected internally by USB