



C9900-E2xx | Slotbox for extending Industrial PCs with two plug-in card slots

The slotbox makes PCI Express and PCI slots available outside the IPC as well. The PCI Express bus is fed via a plug connector and cable to a slotbox located up to 7 m (23-ft) away. Users can use the installation space in the control cabinet flexibly and locate further plug-in cards locally.

Both PCI and PCI Express card slots are available by using different versions of the slotbox. The slotbox is made of sturdy aluminium and ideal for use in industrial environments.



Technical data	C9900-E249	C9900-E250	C9900-E251
	fanless aluminium housing for control cabinet installation		
	2 slots for up to 190 mm long plug-in cards		
	all connectors on the top		
	PCIe x1 input for connection with an Industrial PC with PCIe module C9900-E236 or -E239		
	7 m max. distance between Industrial PC and slotbox		
	1 PCI and 1 PCIe x1 slot	2 PCIe x1 slots	2 PCI slots
	IP 20		
	operating temperature 0...55 °C		
	weight without plug-in cards 1.7 kg		
	dimensions (W x H x D) 94 x 222 x 132 mm (3.7" x 8.7" x 5.2") without mounting plate		
	24 V DC power supply		

Accessories	
C9900-E236	PCIe modules with external PCIe x1 connector for C5210, CP62xx or C65xx with PCIe module slot
C9900-E239	PCIe modules with external PCIe x1 connector for C6930
C9900-K501	connecting cable PCIe x1 external, 1 m
C9900-K502	connecting cable PCIe x1 external, 3 m
C9900-K503	connecting cable PCIe x1 external, 5 m
C9900-K504	connecting cable PCIe x1 external, 7 m