



## KL9182 | Potential distribution terminal with 16 terminal connections

The potential distribution terminal KL9182 provides 16 terminal points for potential distribution and enables the voltage to be picked up without further bus terminal blocks or wiring. The power contacts are fed through to the next terminal without connecting to the terminal points.

The HD Bus Terminals (High Density) with increased packing density feature 16 connection points in the housing of a 12 mm Bus Terminal. The conductors can be connected without tools in the case of solid wires using a direct plug-in technique.

Technical data	KL9182
Number of separate potentials	8
Terminal points per potential	2
Current load	max. 10 A (per terminal point)
Power LED	–
Defect LED	–
Current consumption K-bus	–
Nominal voltage	≤ 60 V AC/DC
Electrical isolation	500 V (K-bus/field potential)
PE contact	–
Shield connection	–
K-bus, looped through	yes
Power contacts looped through	yes (2 power contacts)
Bit width in the process image	–
Electrical connection to DIN rail	–
Electrical connection to power contacts	–
Configuration	no address or configuration setting
Special features	8 x 2-way bridges
Weight	approx. 60 g
Operating/storage temperature	0...+55 °C/-25...+70 °C
Relative humidity	95 %, no condensation
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4
Protect. class/installation pos.	IP 20/variable
Approvals	CE, UL