



TF3300 | TC3 Scope Server

The TwinCAT 3 Scope Server prepares data for visual display in the TwinCAT 3 Scope View. It can be used for autarkic data recordings in distributed systems within production, plant or machine networks. The Scope Server not only features TwinCAT-specific communication interfaces, it also offers support for the OPC UA communication standard.



Technical data	TF3300
Required	TC1000
Target system	Windows 7/8/10

Ordering information	
TF3300-0v40	TC3 Scope Server, platform 40 (Performance)
TF3300-0v50	TC3 Scope Server, platform 50 (Performance Plus)
TF3300-0v60	TC3 Scope Server, platform 60 (Mid Performance)
TF3300-0v70	TC3 Scope Server, platform 70 (High Performance)
TF3300-0v80	TC3 Scope Server, platform 80 (Very High Performance)
TF3300-0v81	TC3 Scope Server, platform 81 (Many-core 5...8 Cores)
TF3300-0v82	TC3 Scope Server, platform 82 (Many-core 9...16 Cores)
TF3300-0v83	TC3 Scope Server, platform 83 (Many-core 17...32 Cores)
TF3300-0v84	TC3 Scope Server, platform 84 (Many-core 33...64 Cores)
TF3300-0v90	TC3 Scope Server, platform 90 (Other)
TF3300-0v91	TC3 Scope Server, platform 91 (Other 5...8 Cores)
TF3300-0v92	TC3 Scope Server, platform 92 (Other 9...16 Cores)
TF3300-0v93	TC3 Scope Server, platform 93 (Other 17...32 Cores)
TF3300-0v94	TC3 Scope Server, platform 94 (Other 33...64 Cores)