


TwinCAT 3 Connectivity



## TF6010 | TC3 ADS Monitor

The free-of-charge TC3 ADS Monitor provides recording und diagnostics functions for the communication of TwinCAT systems. It is integrated into the TwinCAT 3 engineering environment. In addition, it can be used to configurate and execute user-specific commands for testing ADS servers.

Technical data	TF6010
Required	TE1000
Target system	Windows 7/8/10

Ordering information	
TF6010-0v40	TC3 ADS Monitor, platform 40 (Performance)
TF6010-0v50	TC3 ADS Monitor, platform 50 (Performance Plus)
TF6010-0v60	TC3 ADS Monitor, platform 60 (Mid Performance)
TF6010-0v70	TC3 ADS Monitor, platform 70 (High Performance)
TF6010-0v80	TC3 ADS Monitor, platform 80 (Very High Performance)
TF6010-0v81	TC3 ADS Monitor, platform 81 (Many-core 5...8 Cores)
TF6010-0v82	TC3 ADS Monitor, platform 82 (Many-core 9...16 Cores)
TF6010-0v83	TC3 ADS Monitor, platform 83 (Many-core 17...32 Cores)
TF6010-0v84	TC3 ADS Monitor, platform 84 (Many-core 33...64 Cores)
TF6010-0v90	TC3 ADS Monitor, platform 90 (Other)
TF6010-0v91	TC3 ADS Monitor, platform 91 (Other 5...8 Cores)
TF6010-0v92	TC3 ADS Monitor, platform 92 (Other 9...16 Cores)
TF6010-0v93	TC3 ADS Monitor, platform 93 (Other 17...32 Cores)
TF6010-0v94	TC3 ADS Monitor, platform 94 (Other 33...64 Cores)