

TwinCAT 3 Connectivity



## TF6220 | TC3 EtherCAT Redundancy 250

TwinCAT EtherCAT Redundancy 250 extends the TwinCAT EtherCAT Master by the possibility to implement cable redundancy for up to 250 EtherCAT devices: from the last logical device a cable is returned back to the master. Configuration and diagnostics take place in the TwinCAT 3 engineering environment.

<b>Technical data</b>	<b>TF6220</b>
Required	TC1100
Target system	Windows 7/8/10, Windows CE

Ordering information	
TF6220-0v40	TC3 EtherCAT Redundancy 250, platform 40 (Performance)
TF6220-0v50	TC3 EtherCAT Redundancy 250, platform 50 (Performance Plus)
TF6220-0v60	TC3 EtherCAT Redundancy 250, platform 60 (Mid Performance)
TF6220-0v70	TC3 EtherCAT Redundancy 250, platform 70 (High Performance)
TF6220-0v80	TC3 EtherCAT Redundancy 250, platform 80 (Very High Performance)
TF6220-0v81	TC3 EtherCAT Redundancy 250, platform 81 (Many-core 5...8 Cores)
TF6220-0v82	TC3 EtherCAT Redundancy 250, platform 82 (Many-core 9...16 Cores)
TF6220-0v83	TC3 EtherCAT Redundancy 250, platform 83 (Many-core 17...32 Cores)
TF6220-0v84	TC3 EtherCAT Redundancy 250, platform 84 (Many-core 33...64 Cores)
TF6220-0v90	TC3 EtherCAT Redundancy 250, platform 90 (Other)
TF6220-0v91	TC3 EtherCAT Redundancy 250, platform 91 (Other 5...8 Cores)
TF6220-0v92	TC3 EtherCAT Redundancy 250, platform 92 (Other 9...16 Cores)
TF6220-0v93	TC3 EtherCAT Redundancy 250, platform 93 (Other 17...32 Cores)
TF6220-0v94	TC3 EtherCAT Redundancy 250, platform 94 (Other 33...64 Cores)

Related products	
TF6221	TC3 EtherCAT Redundancy 250+