

TwinCAT 3 Industry specific



TF8010 | TC3 Building Automation Basic

The TC3 Building Automation Basic software library allows the implementation of all functions which are important for room automation. Among these are lighting (constant light control, light dimmer...), facade control, scaling functions, filter blocks, timer functions and peak load limiter for energy optimisation.

Technical data	TF8010
Required	TC1200
Target system	Windows 7/8/10, Windows CE

Ordering information	
TF8010-0v20	TC3 Building Automation Basic, platform 20 (Economy)
TF8010-0v30	TC3 Building Automation Basic, platform 30 (Economy Plus)
TF8010-0v40	TC3 Building Automation Basic, platform 40 (Performance)
TF8010-0v50	TC3 Building Automation Basic, platform 50 (Performance Plus)
TF8010-0v60	TC3 Building Automation Basic, platform 60 (Mid Performance)
TF8010-0v70	TC3 Building Automation Basic, platform 70 (High Performance)
TF8010-0v80	TC3 Building Automation Basic, platform 80 (Very High Performance)
TF8010-0v81	TC3 Building Automation Basic, platform 81 (Many-core 5...8 Cores)
TF8010-0v82	TC3 Building Automation Basic, platform 82 (Many-core 9...16 Cores)
TF8010-0v83	TC3 Building Automation Basic, platform 83 (Many-core 17...32 Cores)
TF8010-0v84	TC3 Building Automation Basic, platform 84 (Many-core 33...64 Cores)
TF8010-0v90	TC3 Building Automation Basic, platform 90 (Other)
TF8010-0v91	TC3 Building Automation Basic, platform 91 (Other 5...8 Cores)
TF8010-0v92	TC3 Building Automation Basic, platform 92 (Other 9...16 Cores)
TF8010-0v93	TC3 Building Automation Basic, platform 93 (Other 17...32 Cores)
TF8010-0v94	TC3 Building Automation Basic, platform 94 (Other 33...64 Cores)