

# ITEM 111490 RPS3131SC100RSFM5

Description	Technical data	Accessories	Downloads

### Features

- Plastic housing
- Emergency stop device with detent mechanism according to EN ISO 13850 and EN 60204-1
- Clamping head for pull rope
- Indication of correct rope tension
- Plug connector M12, 5-pin, right
- Switching elements with 2 switching contacts
- Emergency stop

### Switching element

**3131** Slow-action switching contact 2 NC  $\ominus$ 

### Approvals



### Mechanical values and environment

Housing material	Reinforced thermoplastic
Weight	
Net	0,8 kg
Ambient temperature	-25 70 °C
Degree of protection	IP67
Mechanical life	$0,1 \times 10^{6}$
Switching principle	Slow-action switching contact
Rope diameter	2 5 mm
Installation position	Any
Number of positively driven contacts	2
Connection	Plug connector M12 <sup>[1]</sup>
Actuating force	100 N

# Electrical connection ratings

Rated thermal current Ith	4 A
Utilization category according to EN 60947-5-1	
AC-15	3A 50V
Short circuit protection according to IEC 60269-1	
(Fuse)	4A gG
Rated insulation voltage Ui	50 V
Rated impulse withstand voltage $U_{\text{imp}}$	1,5 kV
Switching current	
at 24V	min.10 mA


### Miscellaneous


Additional feature

Emergency stop function


[1] 5-pin (without PE) – right

# **Dimension drawing**






RPS3131SC...LSFM5




RPS3131SC...RSFM5

# Legende

1 265...317 (adjustable via S)






### Legende

1 Detent mechanism Switching-point tolerance ±0.5 mm

### Mounting accessories




**096251** RPS-P-7-70 Features

> Pulley Ø 14mm

Rope set for rope pull switches





### Function expansion

Built-in LED

D

**087423** EINBAULEUCHTE LED M20X1,5



#### Connection material

Connection cable with straight plug connector M12, 5-pin, 5m



**100183** C-M12F05-05X034PV05,0-MA-100183

- Features
- > M12 female plug, 5-pin
- Straight plug connector
- > PVC cable
- > Cable length 5 m
- > With flying lead

Connection cable with plug connector M12, 5-pin, 10m

**100184** C-M12F05-05X034PV10,0-MA-100184

- Features
- > M12 female plug, 5-pin
- > Straight plug connector
- > PVC cable
- > Cable length 10 m
- > With flying lead

Connection cable with plug connector M12, 5-pin, 20m



**100185** C-M12F05-05X034PV20,0-MA-100185

Features

- > M12 female plug, 5-pin
- > Straight plug connector
- > PVC cable
- > Cable length 20 m
- > With flying lead

### Connection cable with 2 plug connectors M12, 5-pin, 5m



**100180** C-M12F05-05X034PV05,0-M12M05-100180

Features

- > M12 female plug to M12 plug connector, 5-pin
- > Straight female plug and plug connector
- > PVC cable
- > Cable length 5 m

Connection cable with 2 plug connectors M12, 5-pin, 10m



**100181** C-M12F05-05X034PV10,0-M12M05-100181

- Features
  - > M12 female plug to M12 plug connector, 5-pin
  - > Straight female plug and plug connector
  - > PVC cable

> Cable length 10 m

Connection cable with 2 plug connectors M12, 5-pin, 20m



**100182** C-M12F05-05X034PV20,0-M12M05-100182 ▼ Features

- > M12 female plug to M12 plug connector, 5-pin
- > Straight female plug and plug connector
- > PVC cable
- > Cable length 20 m

#### Instructions

Betriebsanleitung Seilzugschalter RPS...

	Doc. no.	Version	Language	Download
Betriebsanleitung Seilzugschalter RPS	2090276	08-01/18		🔁 2.7 MB
Operating Instructions for Rope Pull Switches RPS	2090276	08-01/18		🔁 2.7 MB

#### **Declaration of conformity**

#### EU-Konformitätserklärung

	Doc. no.	Version	Language	Download
EU-Konformitätserklärung Declaración UE de conformidad Déclaration UE de conformité	2091952	03-04/17		🔁 0.2 MB
Dichiarazione di conformità EU declaration of conformity				