

AO000421

LED-LIGHTS • ADDITIONAL LIGHTS FOR CAMERA SYSTEMS

For any kind of inspection tasks with a camera sensor the lighting is essential, as only high-contrast images enable reproducible evaluations. Here the lighting has a decisive influence. The choice depends on different factors such as the distance to the test object, its size, the component criteria to be tested or the expected environmental conditions.

MECHANICAL DATA

Ambient temperature (MAX)	50 °C
Degree of protection (IP)	IP41
Front screen material	Acrylic glass
Height	15 mm
Housing design	Cuboid
Housing material	Aluminium
Length	28 mm
Width	241 mm

ELECTRICAL DATA

Max. current consumption	100 mA
Nominal supply voltage	24 V 24 V
Number of pins	4
Type of electrical connection	Connector M8
Voltage type	DC

OPTICAL DATA


Actual camera illumination	Yes
Color temperature	6500 K
Light source	White light
Light version	Line lights
Number of LEDs	32
Radiation angle	120 °

OTHER DATA

• · · · <u>· · · · · · · · · · · · · · · ·</u>	
Changeable fronts	Yes



CONNECTION



Colors: 1 = BN (brown), 2 = WH (white), 3 = BU (blue), 4 = BK (black)

Functions: 1 = L+, 2 = n. c., 3 = L-, 4 = n. c.

DIMENSIONAL DRAWING

INSTALLATION DISPOSAL



Mounting / Installation may only be carried out by a qualified electrician!



SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!