

### AO000468

### **LED-LIGHTS • ADDITIONAL LIGHTS FOR CAMERA SYSTEMS**

For any kind of inspection tasks with a camera sensor the lighting is essential, as only high-contrast images enable reproducible evaluations. Here the lighting has a decisive influence. The choice depends on different factors such as the distance to the test object, its size, the component criteria to be tested or the expected environmental conditions.



# **MECHANICAL DATA**

Ambient temperature (MAX)	50 °C
Degree of protection (IP)	IP41
Front screen material	Acrylic glass
Height	15 mm
Housing design	Rod
Housing material	Aluminium
Length	28 mm
Width	129 mm

# **ELECTRICAL DATA**

Max. current consumption	50 mA
Nominal supply voltage	24 V 24 V
Number of pins	4
Type of electrical connection	Connector M8
Voltage type	DC

### **OPTICAL DATA**


Actual camera illumination	Yes
Color temperature	6500 K
Lamp	LED
Light source	White light
Light version	Line lights
Number of LEDs	16
Radiation angle	120 °
With lamp	Yes

### **OTHER DATA**

Changeable fronts	Yes
5.15.16	



### **CONNECTION**



**Colors:** 1 = BN (brown), 2 = WH (white), 3 = BU (blue), 4 = BK (black)

**Functions:** 1 = L+, 2 = n. c., 3 = L-, 4 = n. c.

# **DIMENSIONAL DRAWING**

INSTALLATION DISPOSAL



Mounting / Installation may only be carried out by a qualified electrician!



# **SAFETY WARNINGS**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!