

#### EM400121

#### **LED-LIGHTS • MACHINE AND BENCH LIGHTS**

LED lights are required in nearly every industrial sector. A lighting coordinated on the respective workplace ensures a better visibility, increases the production quality, the working safety and helps additionally to safe energy costs. Their long lifetime, which is independent of switching cycles, reduces maintenance costs and increases the availability. LED lights are used for the illumination of workplaces, work areas of machines, control cabinets and several other fields of application.



## **MECHANICAL DATA**

Ambient temperature	-20 °C 50 °C
Degree of protection (IP)	IP67
Diameter	40 mm
Front screen material	Safety glass
Housing design	Pipe
Housing material	Aluminium
Length	540 mm
Wet area	Yes

## **ELECTRICAL DATA**

Lamp power	16 W
Luminous flux	1680 lm
Max. current consumption	1250 mA
Nominal supply voltage	20 V 28 V
Number of pins	4
Protection class	III
Type of electrical connection	Connector M12
Voltage type	DC

# **OPTICAL DATA**


Actual camera illumination	No
Color temperature	5000 K
Illuminance at 500 mm distance	2160 lx
Illumination in the center (distance 1 m)	540 lx
Lamp	LED
Light source	Neutral white
Light version	Machine light
Radiation angle	90 °
With lamp	No



#### **OTHER DATA**

Harsh environmental conditions	Yes
Risk groups	0


## **CONNECTION**




**Colors:** 1 = BN (brown), 2 = WH (white), 3 = BU (blue), 4 = BK (black)

**Functions:** 1 = L+, 2 = n. c., 3 = L-, 4 = n. c.

## **DIMENSIONAL DRAWING**





## **INSTALLATION**



Mounting / Installation may only be carried out by a qualified electrician!

## **DISPOSAL**



#### **SAFETY WARNINGS**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!