

ER1E0140

LED-LIGHTS • ADDITIONAL LIGHTS FOR CAMERA SYSTEMS

For any kind of inspection tasks with a camera sensor the lighting is essential, as only high-contrast images enable reproducible evaluations. Here the lighting has a decisive influence. The choice depends on different factors such as the distance to the test object, its size, the component criteria to be tested or the expected environmental conditions.



MECHANICAL DATA

| Ambient temperature | 5 °C 45 °C |
|---------------------------|---------------|
| Degree of protection (IP) | IP67 |
| Diameter | 156 mm |
| Front screen material | Acrylic glass |
| Housing design | Round |
| Housing material | Aluminium |
| Length | 39 mm |
| Wet area | Yes |

ELECTRICAL DATA

| Dimmable | Yes |
|-------------------------------|---------------------|
| Max. current consumption | 1000 mA |
| Nominal supply voltage | 19 V 30 V |
| Number of pins | 12 |
| Protection class | III |
| Type of electrical connection | Cable connector M16 |
| Voltage type | DC |

OPTICAL DATA

| Actual camera illumination | Yes |
|----------------------------|-------------|
| Lamp | LED |
| Light source | White light |
| Light version | Ring lights |
| Number of LEDs | 16 |
| With lamp | Yes |

OTHER DATA


| Changeable fronts | Yes |
|--------------------------------|-----|
| Harsh environmental conditions | Yes |



CONNECTION



DIMENSIONAL DRAWING



INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL



SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!