

FI520271

FILLING LEVEL SENSORS • INDUCTIVE

Filling level and level sensors operate according to different measuring principles. The selection of the sensor depends on the medium to be detected and the ambient conditions. The material flow in a vibratory bowl can be excellently queried with inductive filling level sensors whose pendulum is moved by the material in the pot. The detection of liquid or solid media is, for instance, possible with capacitive filling level sensor technology. These work according to the principle of the condensator, the medium changes the dielectricity between two electrodes. The resulting change is converted into a digital output signal. A further alternative for the detection of filling levels of conductive media is provided by conductive filling level relays. The resistance between reference and measuring electrode is determined. If a set threshold is exceeded, a relay output switches.



o determined in a set timeshold is exceeded, a relay output switches

MECHANICAL DATA


Ambient temperature (MAX)	50 °C
Degree of protection (IP)	IP67
Depth	14 mm
Height	21 mm
Housing design	Cuboid
Housing material	Polyamid
Pendulum length	200 mm
Sensing element material	Plastic
Sensor height	21 mm
Sensor length	14 mm
Sensor width	52 mm
Width	52 mm

ELECTRICAL DATA

LLLCTRICAL DATA	
Max. output current	0.2 A
No-load current	15 mA
Number of contacts as normally closed contact	1
Number of pins	3
Physical measurement principle	Inductive
Rated control supply voltage Us at DC	10 V 30 V
Reverse polarity protection	Yes
Short-circuit-proof	Yes
Type of electrical connection	Connector M8
Type of switching function	Breaker contact
Type of switching output	PNP
Voltage drop	2 V
Voltage type for actuation	DC
With LED display	Yes




CONNECTION



Colors: 1 = BN (brown), 3 = BU (blue), 4 = BK (black)

Functions: 1 = L+, 3 = L-, 4 = PNP NC

DIMENSIONAL DRAWING



INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL



SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!