

## MZ07C199

#### **MAGNETIC SENSORS • SENSORS FOR PNEUMATIC CYLINDERS**

For many tasks in the field of automation technology, it is necessary to recognize the motional processes in pneumatic and hydraulic cylinders and to detect the position of the piston with precision. For this, magnetic cylinder sensors are used.



## **MECHANICAL DATA**

Ambient temperature	25 °C 130 °C
Cable length	0.3 m
Degree of protection (IP)	IP67
Housing design	Cuboid
Housing material	Aluminium
Increased ambient temperatures > 80°C	Yes
Material of cable sheath	Teflon
Metal housing	Yes
Mounting access, cylinder groove	From the top
Number of wires	3
Sensor height	6.5 mm
Sensor length	27 mm
Sensor surface position	Center of the device
Sensor width	5 mm
Strong vibration / motion	Yes

#### **ELECTRICAL DATA**




## **ELECTRICAL DATA**

Short-circuit-proof	Yes
Suitable for safety functions	No
Switching frequency	1000 Hz
Two switching points	No
Type of electrical connection	Cable connector M8
Type of switching function	Normally open contact
Type of switching output	PNP
Voltage drop	2 V
Voltage type	DC
With LED display	No
With monitoring function of downstream devices	No

## **OTHER DATA**

Cylinder sensors	Yes
Cylinder version	With T-groove
Harsh environmental conditions	Yes
Metallic sensor surface	No
Oil and cooling lubricants	Yes
Short travel path	No


## **CONNECTION**



Colors: 1 = BN (brown), 3 = BU (blue), 4 = BK (black)

**Functions:** 1 = L+, 3 = L-, 4 = PNP NO

# **DIMENSIONAL DRAWING**



INSTALLATION DISPOSAL





Mounting / Installation may only be carried out by a qualified electrician!



#### **SAFETY WARNINGS**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!