


**OG50C536****OPTICAL SENSORS • FORK LIGHT BARRIERS**

Special design of through-beam sensor. Transmitter and receiver are located in the fork or angular limbs and are perfectly aligned to each other.

**MECHANICAL DATA**

Ambient temperature	-10 °C ... 60 °C
Degree of protection (IP)	IP67
Fork depth	55 mm
Fork light barrier design	Furcate
Fork width	50 mm
Housing design	Cuboid
Housing material	Zinc die-cast
Material of cable sheath	PUR (Polyurethane)
Material of optical surface	Plastic
Reflector included in the scope of delivery	No
Sensor height	70 mm
Sensor length	10 mm
Sensor width	80 mm

**ELECTRICAL DATA**

Analogue output 0 mA ... 20 mA	No
Analogue output 0 V ... 10 V	No
Analogue output -10 V ... +10 V	No
Analogue output 4 mA ... 20 mA	No
Decay time	0.12 ms
Hysteresis	0.25 mm
Max. output current	200 mA
Max. switching distance	50 mm
No-load current	30 mA
Number of pins	3
Operating voltage	10 V ... 35 V
Pre-failure message	No
Rated control supply voltage $U_s$ at DC	10 V ... 35 V
Relative repeat accuracy	0.1 mm
Repeatability +/-	100 $\mu$ m
Response time	0.12 ms

**ELECTRICAL DATA**

Scanning function	Dark switching
Setting procedure	Manual adjustment
Suitable for safety functions	No
Switching frequency	4000 Hz
Type of electrical connection	Cable
Type of switching function	Normally closed contact/normally open contact
Type of switching output	PNP
Type of the forked light barrier	Standard
Voltage drop	2.8 V
Voltage type	DC
With communication interface, analog	No
With communication interface, AS-Interface	No
With communication interface, CANOpen	No
With communication interface, DeviceNet	No
With communication interface, Ethernet	No
With communication interface, INTERBUS	No
With communication interface, PROFIBUS	No
With communication interface, RS-232	No
With communication interface, RS-422	No
With communication interface, RS-485	No
With communication interface, SSD	No
With communication interface, SSI	No
With monitoring function of downstream devices	No
With other analog output	No
With restart lock	No
With time function	No

**OPTICAL DATA**

Laser protection class	None
Light beam form	Point
Light source	Polarity free red light
Min. object size	0.5 mm
Resolution	500 µm
Wavelength of the sensor	660 nm

**OTHER DATA**

Feeding technology	Yes
--------------------	-----

**DIMENSIONAL DRAWING**

**INSTALLATION**

**DISPOSAL**



Mounting / Installation may only be carried out by a qualified electrician!



## SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!