OL100370

FIBER OPTIC SENSORS • FIBER OPTIC AMPLIFIERS

Fiber optics in combination with the appropriate fiber optic amplifier function as contactless and wear-free position switches that can also be used in harsh environmental conditions. They detect objects independent of their characteristics (e.g., shape, color, surface structure, material). Because the ends and heads of the fiber optics have small dimensions and the fiber optics are flexible, very elegant solutions can be created for detecting objects in places that are difficult to access. Fiber optics can be used without special precautions in potentially explosive areas and in zones with electrical and/or magnetic fields (high-voltage installations, electrical welding equipment) as their function is not thereby affected. Fiber optics are available in versions for implementing the function as through-beam sensor or diffuse reflection sensor.



MECHANICAL DATA

Ambient temperature	-10 °C 55 °C
Amplifier height	30 mm
Amplifier length	64.5 mm
Amplifier width	9 mm
Degree of protection (IP)	IP40
Housing design	Cuboid
Housing material	PBT
Type of mechanical connection	Clamped terminal connection
ELECTRICAL DATA	
Analogue output 0 mA 20 mA	No
Analogue output 0 V 10 V	No
Analogue output -10 V +10 V	No
Analogue output 4 mA 20 mA	No
Connection amplifier with interference suppression	Yes
Max. output current	100 mA
No-load current	30 mA
Number of pins	4
Operating voltage	12 V 24 V
Rated control supply voltage Us at DC	12 V 24 V
Response/decay time	0.6 ms
Reverse polarity protection	Yes
Scanning function	Light-/dark-on mode
Setting procedure	Teach-In
Setting via teach-in	Yes
Short-circuit-proof	Yes
Switching frequency	2000 Hz
Time function	Yes
Type of electrical connection	Connector M8




ELECTRICAL DATA

Type of switching output	PNP
Voltage drop	1.5 V
Voltage type	DC
With blanking function	Yes
With LED display	Yes
OPTICAL DATA	
Light source	Polarity free red light

Mayolongth	of the sensor
wavelength	or the sensor

Polarity free red light 632 nm

DIMENSIONAL DRAWING



INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL



SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!