

OT184103

OPTICAL SENSORS • DIFFUSE REFLECTION SENSORS WITH INTENSITY DIFFERENCIATION

Optical sensors function contactlessly. They detect objects independent of their characteristics (e.g., shape, color, surface structure, material). The basic operating principle is based on the transmission and reception of light. There are three different versions: 1. The through-beam sensor consists of two separate devices, a transmitter and a receiver that are aligned with one another. If the light beam between the two devices is interrupted, the switching output integrated in the receiver changes its status. 2. With the retro-reflective sensor, the transmitter and receiver are located in one device. The emitted light beam is reflected back to the receiver by a reflector that is to be mounted opposite the device. As soon as the light beam is interrupted, the switching output integrated in the device changes its status. 3. With the diffuse reflection sensor, the transmitter and receiver are in one device. The emitted light beam is reflected by the object that is to be detected. As soon as the receiver detects the reflected light, the switching output integrated in the device changes its status.



MECHANICAL DATA

Ambient temperature	-25 °C ... 55 °C
Cable length	2 m
Degree of protection (IP)	IP67
Housing design	Cylinder, screw-thread
Housing material	Plastic ABS
Material of cable sheath	PVC
Material of optical surface	PMMA
Number of wires	3
Reflector included in the scope of delivery	No
Sensor length	65 mm
Storage temperature	70 °C
Storage temperature	-25 °C
Thread length	42 mm
Thread pitch	1 mm
Thread size, metric	18
Wire cross section	0.34 mm ²
With interchangeable lens	No

ELECTRICAL DATA

Alarm output	No
Decay time	20 ms
High repeat accuracy	No
Interference suppression	No
Max. output current	100 mA
Max. switching distance	80 mm
No-load current	10 mA
Number of switching outputs	1

ELECTRICAL DATA

Operating voltage	15 V ... 264 V
Pre-failure message	No
Response time	20 ms
Reverse polarity protection	Yes
Scanning function	Light switching
Sensing range	10 mm ... 80 mm
Suitable for safety functions	No
Switching frequency	25 Hz
Type of electrical connection	Cable
Type of switching function	Normally open contact (NO)
Voltage type	AC
With communication interface, RS-232	No
With LED display	Yes
With monitoring function of downstream devices	No
With other analog output	No
With restart lock	No
With time function	No

OPTICAL DATA

Light beam form	Point
Light exit	IV000197
Light source	Infrared light
Line scanner	No
Small light beam diameter	No
Wavelength of the sensor	880 nm

OTHER DATA

	No
	No
Feeding technology	Yes

DIMENSIONAL DRAWING

INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL



SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!

