

OT570900

OPTICAL SENSORS • DIFFUSE REFLECTION SENSORS WITH INTENSITY DIFFERENCIATION

Radar sensors are used primarily as signal transducers for controlling automatic doors and gates. They detect the movement of persons and/or industrial trucks and, at the same time, are insensitive to soiling. Objects can be detected depending on their movement direction in order to optimize the opening cycles of the gates. In doing so, it is possible to mask out people so that the sensor responds only when vehicles approach. Furthermore, it is possible to eliminate interference caused by moving objects within the detection range of the sensor. Systems that are also equipped with presence detection monitor the area in front of a gate in order to prevent the gate leaf from coming into contact with vehicles or objects.



MECHANICAL DATA

Ambient temperature	-25 °C ... 55 °C
Cable length	10 m
Housing material	Plastic
Inclination angle	-7 ° ... 4 °
Installation height	4000 mm
Installation height	2000 mm
Mounting height	3 m
Number of wires	8
Optimum mounting height	3 m
Sensor height	58 mm
Sensor length	49 mm
Sensor width	208 mm
Suitable for degree of protection (IP)	IP54
Version	Presence detector

ELECTRICAL DATA

For control of industrial doors and gates	Yes
Holding time	1 s
Holding time	0.3 s
Max. output current	100 mA
Number of pins	8
Number of switching outputs	2
Operating voltage	12 V ... 24 V
Power consumption	2.5 W
Reaction time	200 ms
Setting procedure	Parameterization
Setting via remote control	Yes
Switching voltage	42 V
Turn-off delay	Yes
Type of electrical connection	Cable with connector

ELECTRICAL DATA

Type of switching function	Normally closed contact/normally open contact
Type of switching output	Relay contact
Voltage type	AC/DC
With LED display	Yes

OPTICAL DATA

Detection range length, infrared	0.6 m
Detection range width, infrared	3 m
Light source	Infrared light
Wavelength of the sensor	875 nm

DIMENSIONAL DRAWING**INSTALLATION**

Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL**SAFETY WARNINGS**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!