

**OV580915**

**HIGH-PERFORMANCE THROUGH-BEAM SENSORS • AMPLIFIERS**



**MECHANICAL DATA**

Degree of protection (IP)	IP40
Depth	78.5 mm
Device design	Field device
Height	75.5 mm
Housing design	Cuboid
Housing material	Plastic
Length	78.5 mm
Mounting method	Pluggable
Width	38.5 mm

**ELECTRICAL DATA**

Galvanic isolation between input and output	No
Galvanic isolation between inputs	No
Galvanic isolation between supply voltage and all other current circuits	No
High performance light barriers	Yes
Inherently safe according to EN 60947-5-6 NAMUR	No
Input voltage tolerance	20 %
Malfunction message output	Yes
No-load current	92 mA
Number of channels	1
Number of pins	11
Output circuit, relay change-over contact	1
Power consumption	2.2 W
Rated supply voltage at DC	24 V ... 24 V
Suitable for safety functions	No
Switching capacity	120 VA
Switching current	5 A
Switching frequency	18 Hz
Switching voltage	24 V
Switching voltage AC	230


## ELECTRICAL DATA

Switching voltage DC	24 V
Turn-off delay	10000 ms
Turn-on delay	10000 ms
Type of electrical connection	Plug-in connection
Type of switching function	Change-over contact (NO/NC)
Type of voltage supply	Active
With LED display	Yes

## OTHER DATA

Operating temperature	-25 °C ... 50 °C
-----------------------	------------------

## DIMENSIONAL DRAWING



## INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!

## DISPOSAL



## SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!