

OV584901

HIGH-PERFORMANCE THROUGH-BEAM SENSORS • AMPLIFIERS



MECHANICAL DATA

Degree of protection (IP)	IP40
Depth	78.5 mm
Device design	Field device
Height	76.5 mm
Housing design	Cuboid
Housing material	Plastic
Length	78.5 mm
Mounting method	Pluggable
Width	40 mm

ELECTRICAL DATA

Galvanic isolation between input and output	No
Galvanic isolation between inputs	No
Galvanic isolation between supply voltage and all other current circuits	No
High performance light barriers	Yes
Inherently safe according to EN 60947-5-6 NAMUR	No
Input voltage tolerance	10 %
Malfunction message output	No
No-load current	26 mA
Number of channels	1
Number of output circuits, transistor npn	1
Number of output circuits, transistor pnp	1
Number of pins	11
Output circuit, relay change-over contact	1
Power consumption	5 W
Rated supply voltage at AC	115 V ... 115 V
Suitable for safety functions	No
Switching current	5 A
Switching frequency	18 Hz
Switching voltage	115 V

ELECTRICAL DATA

Switching voltage AC	230
Switching voltage DC	24 V
Type of electrical connection	Plug-in connection
Type of switching function	Change-over contact (NO/NC)
Type of voltage supply	Active
With LED display	Yes

OTHER DATA

Operating temperature	-25 °C ... 60 °C
-----------------------	------------------

DIMENSIONAL DRAWING**INSTALLATION**

Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL**SAFETY WARNINGS**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!