

SL180100

FLOW SENSORS • SENSORS FOR AIR

The function of the flow sensor is based on the calorimetric principle. The probe is heated up from the inside a few degrees Celsius in relation to the flow medium, in which it protrudes. When the medium flows, the heat generated in the probe is dissipated through the medium. The temperature within the sensor is measured and compared with the likewise measured medium temperature. From the obtained temperature difference the flow state of each medium can be derived. These sensors are applied in areas such as monitoring of cooling systems, ventilation systems, pump dry running by checking the presence of liquid or gas flows.



MECHANICAL DATA

Cable length	2 m
Degree of protection (IP) of evaluation electronics	IP67
Degree of protection (IP) of measuring head	IP67
Depth	82 mm
Housing design	Cylinder, screw-thread
Housing material	PBT
Material of cable sheath	PVC
Number of wires	3
Thread length	61 mm
Thread pitch	1 mm
Thread size, metric	18
Type of process connection	IV000299

0.5 m/s 15 m/s
Yes
No
200 mA
Calorimetric
70 mA
24 V 24 V
40 ms
20 %
2000 ms
Yes
Manual adjustment
Yes
Cable
Normally open contact (NO)
PNP
2 V




ELECTRICAL DATA

Voltage type	DC
With LED display	Yes

OTHER DATA

Suitable for gases	Yes
Suitable for liquids	No


CONNECTION



Colors: 1 = BN (brown), 3 = BU (blue), 4 = BK (black)

Functions: 1 = L+, 3 = L-, 4 = PNP NO

DIMENSIONAL DRAWING



INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL



SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!