

### SS90C327

# **FLOW SENSORS • SENSORS FOR WATER**

The function of the flow sensor is based on the calorimetric principle. The probe is heated up from the inside a few degrees Celsius in relation to the flow medium, in which it protrudes. When the medium flows, the heat generated in the probe is dissipated through the medium. The temperature within the sensor is measured and compared with the likewise measured medium temperature. From the obtained temperature difference the flow state of each medium can be derived. These sensors are applied in areas such as monitoring of cooling systems, ventilation systems, pump dry running by checking the presence of liquid or gas flows.



### **MECHANICAL DATA**

2 m
IP67
IP67
Cylinder, screw-thread
Stainless steel 1.4571
Yes
10 °C 160 °C
4
60 bar
Stainless steel 1.4571
31 mm
G1/2 inch
0.25 mm²
1 m/s 40 m/s
0.01 m/s 3 m/s
Yes
3 m/s
0.01 m/s
No
100 m
Calorimetric
60 bar
20 ms
20000 ms
Cable
Yes



# **OTHER DATA**

For pneumatic applications	Yes
Suitable for gases	Yes
Suitable for liquids	Yes

#### DIMENSIONAL DRAWING

# INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!





### SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!