

UT120021

ULTRASONIC SENSORS • DISTANCE MEASUREMENT

Ultrasonic sensors are non-contact and wear-free position switches which can also be used under rough environmental conditions. A key advantage of these devices lies in the fact that the material and the surface characteristics of the objects to be detected can be almost anything. Solids, liquids, grainy materials and powdery materials can be identified without the shape or the color of the object having any influence to the measured result. In addition, the ability to detect transparent materials such as films and fluids is of particular importance. The shape and color of the objects do not influence the result of the detection. The capability to detect transparent films or liquids is also of special importance. Ultrasonic sensors are used for distance measurement (e.g. detection of diameters, loop control), for fill level detection (e.g. silo detection), for positioning and presence detection (e.g. glass pane positioning, film tear check, glass bottle detection)



MECHANICAL DATA

Ambient temperature	-10 °C ... 60 °C
Degree of protection (IP)	IP67
Diameter detection	Yes
Housing coating	Nickel-plated
Housing design	Cylinder, screw-thread
Housing material	Brass
Housing material, detail	Nickel-plated brass
Sensor length	88 mm
Thread length	42.5 mm
Thread pitch	1 mm
Thread size, metric	12

ELECTRICAL DATA

Adjustable measuring range	Yes
Carrier frequency	380 kHz
Distance measuring sensors	Yes
Filling level measurement	Yes
Measuring range length	2 mm ... 82 mm
No-load current	35 mA
Number of pins	4
Relative repeat accuracy	0.1 %
Reverse polarity protection	Yes
Setting procedure	Teach-In
Setting via teach-in	Yes
Short-circuit-proof	Yes
Sound outlet	Axial
Supply voltage	15 V ... 30 V
Synchronization possible	No

ELECTRICAL DATA

Temperature drift	2 %
Type of analog output	0 V ... 10 V
Type of electrical connection	Connector M12
Voltage type	DC
With LED display	Yes
With LED display (measuring range)	Yes


OPTICAL DATA

High resolution	Yes
Resolution	0.3 mm

OTHER DATA

Level detection	Yes
-----------------	-----

DIMENSIONAL DRAWING



 sichere Erkennung eines Objektes von 15x15mm

UT120021

INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL



SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!