


VC024901

MISCELLANEOUS • CAR DETECTORS



MECHANICAL DATA

Degree of protection (IP)	IP40
Depth	77 mm
Device design	Field device
Height	75 mm
Housing design	Cuboid
Housing material	Plastic
Length	77 mm
Mounting method	Pluggable
Width	40 mm

ELECTRICAL DATA

Amplifier for induction loops	Yes
Galvanic isolation between input and output	No
Galvanic isolation between inputs	No
Galvanic isolation between supply voltage and all other current circuits	No
Inherently safe according to EN 60947-5-6 NAMUR	No
Malfunction message output	No
No-load current	100 mA
Number of channels	2
Number of pins	11
Output circuit, relay change-over contact	2
Power consumption	2.5 W
Rated supply voltage at AC	240 V ... 220 V
Suitable for safety functions	No
Switching capacity	1150 VA
Switching current	5 A
Switching voltage	250 V
Switching voltage AC	230
Type of electrical connection	Plug-in connection
Type of switching function	Change-over contact (NO/NC)

ELECTRICAL DATA

Type of voltage supply

Active

With LED display

Yes

OTHER DATA

Operating temperature

-30 °C ... 40 °C

DIMENSIONAL DRAWING**INSTALLATION**

Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL**SAFETY WARNINGS**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!