

## VKA000L4

### CONNECTION TECHNOLOGY • CABLE SOCKETS /CONNECTORS ONE-SIDED PRE-ASSEMBLED

ipf cable sockets are used primarily for establishing the electrical connection of sensors. Their features are characterized by rugged design, the highest protection classes (IP67 | IP68 | IP69K) and, if desired, with 360° shielding. With the features: bus-ready, suitable for use with drag chains and robots, resistance to oil and chemicals, resistance to welding sparks, their resistance to cleaning agents or high-pressure and steam-jet cleaning, the expanded temperature range of up to +230°C, the rapid interconnection technology and special data transmission properties, the cable sockets meet all requirements in automation technology.



#### MECHANICAL DATA

Cable length	10 m
Increased ambient temperature > 90°C	Yes
Number of wires	3
Perm. ambient temperature of cable, fixed cable	-40 °C ... 180 °C
Positioning of cable feed, field side	Straight
Suitable for trailing chain	Yes

#### ELECTRICAL DATA

Number of pins	3
Shielded	No
Type of plug-in contact, field side	Female (socket)
With LED display	No

#### OTHER DATA

Flame resistant	No
Halogen-free	No
IR-networked	No
Suitable for trailing chain and torsion resistant	Yes

#### CONNECTION



**Colors:** 1 = BN (brown), 2 = BK (black), 3 = BU (blue)

**Functions:**

#### DIMENSIONAL DRAWING

## INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!

## DISPOSAL



## SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!