


VKA01034

CONNECTION TECHNOLOGY • CABLE SOCKETS / CONNECTORS ONE-SIDED PRE-ASSEMBLED

ipf cable sockets are used primarily for establishing the electrical connection of sensors. Their features are characterized by rugged design, the highest protection classes (IP67 | IP68 | IP69K) and, if desired, with 360° shielding. With the features: bus-ready, suitable for use with drag chains and robots, resistance to oil and chemicals, resistance to welding sparks, their resistance to cleaning agents or high-pressure and steam-jet cleaning, the expanded temperature range of up to +230°C, the rapid interconnection technology and special data transmission properties, the cable sockets meet all requirements in automation technology.



MECHANICAL DATA

Cable length	10 m
Degree of protection (IP)	IP67
Number of wires	3
Perm. ambient temperature of cable, fixed cable	-25 °C 80 °C
Positioning of cable feed, field side	Straight
Positioning of cable feed, housing side	Straight
Suitable for trailing chain	Yes
Wire assembly	19 x 0.16mm
Wire cross section	0.34 mm²

ELECTRICAL DATA

Flow resistance	5 mOhm
Line diameter	5 mm
Number of pins	3
Rated current In	4 A
Rated voltage	250 V
Type of electrical connection, field side	MC
Type of electrical connection, housing side	Free conductor end
Type of plug-in contact, field side	Female (socket)
With LED display	No

OTHER DATA

OTHER DATA	
IR-networked	No

DIMENSIONAL DRAWING

INSTALLATION DISPOSAL





Mounting / Installation may only be carried out by a qualified electrician!



SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!