# **Mounting flange**



### **Model Number**


#### BF 12-F

Plastic mounting adapter, 12 mm

#### Features

- ٠ For mounting cylindrical sensors with metal thread
- Secure mounting of the sensor via a snap lock
- Installation position defined by fixed stop
- Adjustable via slot mounting ٠

### Dimensions



### **Technical data**

General specifications	
Incido diamotor	

Ambient conditions

- Ambient temperature
- Mechanical specifications Material Construction type

-25 ... 85 °C (-13 ... 185 °F)

12 mm

black polycarbonate (PC) For sensors with 45° chamfer

## Note

### Installation

- · Position the mounting bracket on the desired place
- ٠ Mark the position of drilling holes in the mid section of the oblong holes
- Drill the mounting holes through the surface •
- Screw on the mounting bracket slightly via the lateral oblong holes by using suitable M4 screws
- Stick the sensor through the mounting bracket and fix the sensor by the lid on the upper . part of the bracket
- Adjust the bracket and make the final positioning
- · Fix the mounting bracket finally with the screws

Pepperl+Fuchs Group

www.pepperl-fuchs.com

Refer to "General Notes Relating to Pepperl+Fuchs Product Information"

USA: +1 330 486 0001 fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 4411 fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091 fa-info@sg.pepperl-fuchs.com



1