



Model Number

SLA29/116

with terminal compartment

Features

- Sensing range up to 30 m
- Self-monitoring (type 4 according to IEC/EN 61496-1)
- Red transmission light
- Integrated alignment aid
- Clearly visible LED functional display and pre-fault indicator on the receiver
- Sturdy housing
- Waterproof, degree of protection IP67
- Operation on control units of SB4 (SafeBox)

Accessories

OMH-05

Mounting aid for round steel $\varnothing$ 12 mm or sheet 1.5 mm ... 3 mm

OMH-21

Mounting bracket

OMH-22

Mounting bracket

OMH-MLV11-K

dove tail mounting clamp

MS SLP/SLA28

Fixing plate


MS SLPCM

Mounting bracket

SLA-1-M

Additional accessories can be found in the Internet.


Dimensions



Electrical connection

Design with terminal compartment

Receiver:



Emitter:

Technical data

System components

Emitter	SLA29-T/116
Receiver	SLA29-R/116

General specifications

Effective detection range	0.2 ... 30 m
Threshold detection range	40 m
Light source	LED
Light type	modulated visible red light
Target size	static: 30 mm dynamic: 40 mm (at $v = 1.6$ m/s of the obstacle)
Alignment aid	LED red in receiver
Angle of divergence	$< 5^\circ$

Functional safety related parameters

Safety Integrity Level (SIL)	SIL 3
Performance level (PL)	PL e
Category	Cat. 4
Mission Time (T_M)	20 a
PFH_d	4.4 E-10
Type	4

Indicators/operating means

Operation indicator	LED green
Function indicator	LED yellow: 1. LED lit constantly: signal $> 2 \times$ switching point (function reserve) 2. LED flashes: signal between $1 \times$ switching point and $2 \times$ switching point 3. LED off: signal $<$ switching point

Electrical specifications

Operating voltage	U_B	Power supply via control unit
-------------------	-------	-------------------------------

Conformity

Functional safety	ISO 13849-1
Product standard	EN 61496-1 ; IEC 61496-2

Ambient conditions

Ambient temperature	-20 ... 60 °C (-4 ... 140 °F)
Storage temperature	-20 ... 70 °C (-4 ... 158 °F)
Relative humidity	max. 95 %, not condensing

Mechanical specifications


Degree of protection	IP67 according to EN 60529
Connection	terminal compartment
Material	
Housing	ABS plastic, RLA 1021 (yellow) painted
Optical face	Plastic pane
Mass	per device 70 g



Approvals and certificates

CE conformity	CE
CCC approval	CCC approval / marking not required for products rated ≤ 36 V
Approvals	TÜV

Curves/Diagrams

Characteristic response curve





Additional information

For much easier alignment even for long distance applications, an additional red LED is located in the receiver's optics:

- LED constantly illuminated:
signal strength < switching level
- LED flashes:
signal strength is between 1-fold switching level and 2-fold switching level
- LED off:
signal strength $\geq$ 2-fold switching level (function reserve)

System accessories

Control units

SC4-2
SB4 (SafeBox)

Cable sockets

Option /73c:

straight: V1-G-2M-PVC
V1-G-5M-PVC
V1-G-10M-PVC
angled: V1-W-2M-PVC
V1-W-5M-PVC
V1-W-10M-PVC

Option /105:



straight: V15-G-2M-PVC
V15-G-5M-PVC
V15-G-10M-PVC
angled: V15-W-2M-PVC
V15-W-5M-PVC
V15-W-10M-PVC

Option /116: no

Mounting aids

OMH-21
OMH-22
OMH-05
OMH-MLV11-K

Further accessories

Laser alignment aid
BA SLA28

Muting Set
MS SLP/SLA28

Redirection mirror
SLA-1-M