




Dimensions



Model Number

V1-G-5M-PUR-TV1-G

Y-splitter cordset, M12 to 2 x M12, 3-pin, PUR cable

Features

- Simple assembling of 2 signals to one M12 plug-in station
- Pins 2 and 4 bridged
- Flame resistant cable
- Resistant to microbes and hydrolysis
- Halogen-free
- Does not give off silicone
- Suitable for drag chains

Technical data

General specifications

Number of pins 3

Electrical specifications

Operating voltage U_B max. 250 V AC/DC
 Operating current I_B max. 4 A
 Volume resistance $< 5 \text{ m}\Omega$

Ambient conditions

Ambient temperature Body: -25 ... 90 °C (-13 ... 194 °F)
 cable, fixed: -40 ... 80 °C (-40 ... 176 °F)
 cable, flexing: -25 ... 80 °C (-13 ... 176 °F)

Mechanical specifications

Degree of protection IP65 / IP68 / IP69K
 Connection 1 x M12 connector, straight
 2 x M12 straight sockets

Material

Contacts CuSn
 Contact surface Ni/Au
 Body TPU, black
 Cable PUR
 Slotted nut Zinc die-casting, nickel-plated
 Sleeve connector Zinc die-casting, nickel-plated
 Seal NBR
 Core insulation PP

Cable


Sheath diameter $\varnothing 4.4 \text{ mm}$
 Bending radius $> 10 \times$ cable diameter, appropriate for conveyor chains
 $> 5 \times$ cable diameter, fixed

Color black
 Cores $3 \times 0.34 \text{ mm}^2$; 22 AWG
 Conductor construction $42 \times 0.1 \text{ mm } \varnothing$
 Length L 5 m

Compliance with standards and directives

Standard conformity
 Degree of protection EN 60529:2000
 Standards IEC 61076-2-101:2008

Electrical connection



Release date: 2015-06-24 12:02 Date of issue: 2015-06-24 261155_eng.xml

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
 www.pepperl-fuchs.com

USA: +1 330 486 0001
 fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 4411
 fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
 fa-info@sg.pepperl-fuchs.com